



HD 9/20-4 MX Plus

Cold-water pressure washer with tough 4-pole low-speed three-phase motor, Dirt blaster nozzle and integrated high-pressure hose reel.


















- Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.
- At last work without getting tired: the EASY!Force high-pressure gun.
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.
- 2 Switch-CHEM
- For accurate and variable cleaning agent dosing.
- 2-way dosing valve for cleaning agent changeover.

3 Powerful and durable

- Air-water-cooled electric motors for intensive use.
- 4-pole low-speed electric motor.

4 Clever features

- Power cord storage at the rear of the unit.
- Integrated lance holder for easy transport.

TECHNICAL DATA AND EQUIPMENT.





HD 9/20-4 MX Plus

- Air/water-cooled motor
- Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.
- 3-piston pump with ceramic pistons

Technical data		
Order Number		1.524-927.0
EAN code		4054278167343
Current type	Ph / V / Hz	3 / 400 / 50
Flow rate	l/h	460-900
Operating pressure	bar / MPa	40-200 / 4-20
Max. pressure	bar / MPa	220 / 22
Max. water feed temperature	°C	60
Power rating	kW	7
Weight (with accessories)	kg	57,6
Dimensions (L x W x H)	mm	554 × 509 × 1000

Equipment		
		2 x 2.5 L
Trigger gun		EASY!Force
High-pressure hose	m	15
Spray lance	mm	1050
Triple nozzle (0°/25°/40°)		Manual
Dirt Blaster spray lance		ı
Integral high-pressure hose reel		I
ANTI!Twist		
Pressure switch control		I
Servo Control		

■ Included in delivery.















		Order Number	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides				,				Ť
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW $10/155^{\circ}$ C/220 bar	
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m			
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m			
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l h. With union on both sides. 2x M 22 x 1.5 with anti-kink	/
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	210 bar	40 m		protection.	
Hose assembly TR DN10 22MPa 10m	11	6.110-041.0	ID 10	220 bar	10 m			
Longlife 400 with unions on both si	des			·				Ť
High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling	12	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 20 m, DN 8, extension	13	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling	14	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	
Standard								ĺ
Hose assembly TR rotatable DN8 31,5MPa 1	15	6.110-018.0	ID 8	315 bar	15 m		High-pressure hose with AVS hose reel connection and EASY!Lock hand screw connection.	

 $[\]blacksquare$ Included in delivery. \qed Available accessories. $\ \, \blacktriangle$ Extension hose.

















		Order Number	Flow rate			Price	Description
Trigger guns				I	I.		
EASY!Force Advanced	1	4.118-005.0					Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.
Conversion kit 1 from high pressure hose	2	4.111-050.0					A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance.
Conversion kit 2 from device	3	4.111-051.0					Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose.
Conversion kit 3 only EASY!Force	4	4.111-052.0					A conversion kit for the EASY!Force gun, which includes the correct adaptors to conncect to the M22 style lance and hose.
Servo Control							
Servo control	5	4.118-008.0	750-1100 l/h				Water quantity and pressure regulated directly from the hand spray gun.
Quick connect							
Quick-fitting pipe union coupler trapezo	6	2.115-000.0					For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.
Quick-fitting pipe union plug nipp- le tra	7	2.115-001.0					Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread.

[■] Included in delivery.

Available accessories.

Extension hose.































		Order Number	Max. working pressure	Length		Price	Description	
Rotating spray lances				ı				
1050 mm lance, rotatable, ergonomic	1	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	•
Nozzle Light	2	2.680-002.0		125 mm			LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results.	
Lance 250 mm, non-rotatable	3	4.112-027.0	300 bar	250 mm			600 mm stainless steel lance (manual coupling) with ergono-	- 🗆
550 mm lance, non-rotatable	4	4.112-024.0	300 bar	400 mm			mic handle for ease of use and protection. Rotatable 360°	
Rotatable lance, 600 mm, ergonomic	5	4.112-007.0	300 bar	600 mm			under pressure.	
Lance 850 mm, rotatable, ergonomic	6	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	-
Lance 1550 mm, rotatable, ergonomic	7	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 2050 mm, rotatable, ergonomic	8	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
Jet pipe extension TR 1000 mm	9	4.112-048.0	300 bar	1000 mm			Spray lance extension with EASY!Lock connection. Length 1000 mm.	
Double lance					,			
Double lance 960 mm	10	2.112-016.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance								
WC and gutter lance	11	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance	ı	1	ľ	1				
Flexible lance 1050 mm	12	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Articulated joint TR 20	13	4.112-057.0	300 bar				For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Telescopic spray lance								
Telescopic jet pipe	14	4.112-037.0	225 bar	5400 mm			Can be continuously extended from 1.8 to 5.4 m. For cleaning areas that are difficult to reach, such as ceilings or facades. With integrated HD trigger gun, M 22 x 1.5 connection with rotary coupling. Connection for M 18 x 1.5 nozzles	
Restraint belt for telescopic jet pipe	15	6.373-987.0					Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.	
Gutter cleaner								
Gutter cleaning lance	16	2.112-015.0		960 mm			The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance								
Underbody lance	17	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	

[■] Included in delivery.

Available accessories.

Extension hose.





		Order Number	Max. working pressure	Length		Price	Description
Additional handle							
Additional handle for EASY!Lock spray lances	18	4.321-380.0					Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.

[■] Included in delivery.

Available accessories.

Extension hose.









		Order Number	Max. working pressure	Nozzle size		Price	Description
Dirt blaster, large							
Dirt blaster - without changeover function	1	4.114-027.0	300 bar	50			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.
Triple nozzles							
Triple nozzle 050	2	4.117-037.0	300 bar	50			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.
Angle vario nozzle 0°-90°							
Spezial nozzle 0005	3	4.113-007.0		50			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.

[■] Included in delivery.

Available accessories.

Extension hose.





		Order Number	Nozzle size		Price	Description
		Order Homber	NOZZIE SIZE		PIICE	Description
HP nozzle spray angle 0°						
High-pressure nozzle spray angle °0	1	2.113-034.0	50			High-pressure nozzle with powerful jet for extremely stubborn dirt.
Power nozzle spray angle 15°						
Power nozzle spray angle 15°	2	2.113-047.0	55			Fan jet nozzle with 15 $^{\circ}$ spray angle suitable for stubborn dirt.
Power nozzle spray angle 25°						
Power nozzle spray angle 25°	3	2.113-023.0	50			Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
Power nozzle spray angle 40°						
Power nozzle spray angle 40°	4	2.113-055.0	55			Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

[■] Included in delivery.

Available accessories.

Extension hose.































				1			\top
		Order Number			Price	Description	
Nozzle union		'	•		 		
Nozzle screws	1	4.112-011.0				Nozzle screws with protectors for high-pressure and power	
Machine-specific nozzle kit with or	der no	3 637-170				nozzles	\vdash
Nozzle insert trapezoidal thread		4.769-011.0				For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP	L
HDS-GER						power nozzle + union	
Nozzle insert with order no. 3.637-	001						
Nozzle insert for Order No. 3.637-	3	4.769-003.0				Nozzle insert for detergent injector 3.637-001 for high-	
001, high-pressure for machines						pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
up to 1100 l/h. Low pressure for units rated up to	4	4.769-001.0				For low pressure with machines up to 1.100 l/h	+
1100 l/h		4.703 001.0				To low pressure with machines up to 1.100 l/m	
Rotary coupling			,				
Rotary coupling	5	4.111-021.0				Kärcher rotary coupling prevents twisting and kinking of	
						high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	
Coupling						Thi. With grip protection.	\vdash
Coupler -2xM22x1,5	6	4.111-037.0				Brass double connector for connecting and extending high-	П
						pressure hoses. With rubber protection. Connector: 2x M 22	
						x 1.5 m.	\perp
Connector			1	ı			
Nozzle connector/screw connector	7	4.111-022.0				Nozzle connector/screw connector for connecting high-	
						pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5	
						and 1x M 18 x 1.5.	
Y distributor	8	4.111-024.0				Offers the option to connect two spray units to the machine	ž. П
						Installation on the high pressure outlet.	
Short spray unit	9	4.111-038.0				For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with	
						triple nozzles.	
Adapter EASY!Lock					 	,,	
Adapter 1 M22AG-TR22AG	10	4.111-029.0				Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	11	4.111-030.0				Adapter 2 to connect the old device with the new hose and	П
						the old gun with the new hose	<u> </u>
Adapter 3 M22IG-TR22AG	12	4.111-031.0				Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter M22 - Swivel	13	4.111-032.0				M22 x 1,5female and swivel connection. For extension of	
						high-pressure hoses with AVS connection or for usage of th	
						telescopic lance with a high-pressure hose with AVS connec	- -
Adapter 5 TR22IG-M22AG	14	4.111-033.0				tion. Adapter 5 to connect the new gun with the old spray lance	+
Adapter 5 TRZZIG WZZAG	14	4.111 055.0				and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	15	4.111-034.0				Adapter 6 to connect the new device with the old hose and	
						the old hose with the new gun	╨
Adapter 7 M18IG-TR20AG	16	4.111-035.0				Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	17	4.111-036.0				Adapter 8 to connect the new spray lance with the old	+
	1,					nozzle	
ADAPTER for replacement TR22IG-	18	4.111-046.0				Rotatable adapter for connecting EASY!Force high-pressure	
M22AG Er						gun and high-pressure hoses with M 22x1.5 connection	

























		1							_
		Order Number	Max. working pressure	Nozzle size	Diame- ter		Price	Description	
Pipe cleaning hose, ID 6						·			
Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar					The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	-
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar					20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar					The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	-
Pipe cleaning nozzle									
Dirt blaster pipe cleaning D21/060	4	4.765-002.0		60	21 mm			The forward-tilted rotating pencil jet removes the most	
Dirt blaster pipe cleaning D30/060	5	4.765-005.0		60	30 mm			stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient hand-ling.	
Pipe cleaning nozzle	6	5.763-019.0		65	16 mm			16 mm pipe cleaning nozzle with internal thread. Various je	
	7	5.763-016.0		60	16 mm			directions for environmentally-friendly cleaning of blocked drains and pipes.	
	8	5.763-021.0		70	30 mm			30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	9	6.415-440.0		65	16 mm			Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
Barrel and tank cleaning									
Barrel cleaner BC 14/12	10	2.112-020.0						The barrel cleaner BC 14/12 is a spray unit for the internal cleaning of containers and drums - in particular oak barrels with a capacity between 225 and 600 liters.	
HKF 50 spray head, brass									
HKF 50 spray head , brass	11	3.631-039.0						Interior cleaning head for barrels and containers with bung-	
HKF 50 spray head, brass	12	3.631-058.0						holes of 50 mm and more.	
Nozzle kit for HKF 50 spray head (3	.631-	009.0 / 3.631-039	9.0)						
Nozzle 030 for dual nozzle opera- tion HKF 50	13	6.415-444.0		30				Nozzle for dual-nozzle operation	
Double handle for exact control of the spray head	14	2.863-036.0						Double handle. Precise control of the spray head	
Screw plug for using a spray head with one nozzle	15	5.411-061.0						Screw plug for using a spray head with one nozzle	

[■] Included in delivery.

Available accessories.

Extension hose.























					Diame-				
		Order Number	Flow rate	Nozzle size	ter	P	Price	Description	
Hard Surface Cleaner FRV 30						'			
Add-on kit rubber lip	1	2.642-910.0						For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	
Extension hose 5 m	2	4.440-939.0						5m extension hose for FRV 30. Connection sleeve included.	
Add-on kit hose attachment	3	2.642-528.0						Suction cup for fixing the suction hose to smooth surfaces.	
Add-on kit dirt trap	4	2.642-532.0						Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
FRV 30	5	2.111-010.0						Surface cleaner with integrated waste water pick-up	
Hard surface cleaner FR 30 ME						'			
FR 30 ME surface cleaner	6	2.111-013.0			300 mm			Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Hard Surface Cleaner FR 50									
FR 50 surface cleaner	7	2.111-023.0			500 mm			Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	
Machine-specific nozzle kit for FR									
Nozzle kit for surface cleaners (type-specific) 850 - 1100 l/h	8	2.640-442.0	850-1100 l/h					Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).	
Machine-specific nozzle kits for F	RV			_					
Nozzle kit 050 - for FRV	9	2.642-433.0		50				Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
Hard surface cleaner FRV 30 Me									
Extension hose FRV 30 Me and FRV 50 Me	10	4.441-040.0						5 m extension hose for FRV 30 Me. Includes connecting adapter.	
FRV 30 Me Surface Cleaner	11	2.111-012.0						Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
Surface Cleaner FR 50 Me									
FRV 50 Me surface cleaner	12	2.111-024.0						Surface cleaning with automatic suction of the dirty water for very large surfaces. Hot water cleaning up to 85°C.	

[■] Included in delivery.

Available accessories.

Extension hose.

















									\top
		Order Number	Flow rate				Price	Description	
Cup foam lance									
Cup foam lance Basic 3	1	4.112-055.0	900-2500 l/h					For high-pressure cleaners with a flow rate of 900-2500 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
Cup foam lance Advanced 025	2	2.112-017.0						Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	
Tank grey only for replacement 1L	3	6.414-050.0						Additional 1-litre cleaning agent container for quick replace ment of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Inno Foam Set									
Inno foam kit with detergent injector	4	2.112-000.0						High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set									
Easy Foam Set with RM injector	5	2.112-010.0						HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	t
Nozzle kits for Inno/Easy Foam Set									
Nozzle kit 090 Inno/Easy kit 700 - 1000 l/h	6	2.111-019.0	700-1000 l/h					Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 I/h. For optimal foam system performance.	
Foam nozzle mounting kit		1	1	1	ı	ı			
Foam nozzle kit	7	2.112-013.0						Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	- 🗆

[■] Included in delivery.

Available accessories.

Extension hose.



















							ı
							ı
							ı
		Order Number	Length		Price	Description	
Automatic, self-winding hose reels							
Wall-mounted hose reel	1	2.639-257.0	15 m				
Add-on kit hose reel plastics	2	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Add-on kit hose reel	3	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Hose reel, automatic, 20 m, painted	4	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Hose reel, automatic, basalt grey- coated	5	6.392-105.0	20 m			Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.	
Hose reel, automatic, 20 m, stain- less steel	6	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS hose reel stainless steel	7	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	
Add-on kit hose reel TR 40m	8	6.392-442.0	40 m			Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	П
Swivel holder	9	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
ABS wall fastening stainless steel	10	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	

[■] Included in delivery.

Available accessories.

Extension hose.











		I		T	1	1	1	
		Order Number	Flow rate	Water feed temperature	Length	Length	Price	Description
Solar cleaning - telescopic lances								
Telescopic rod complete 14m	1	4.110-002.0		max. 60 °C				Full carbon telescopic rod for maximum rigidity with minimal weight. With 14 m max. reach and practical quick-release couplings for easy extension and retraction.
Telescopic rod complete 10m CFK	2	4.110-007.0		max. 60 °C				The full carbon telescopic lance offers maximum rigidity with minimal weight. It has a reach of up to 10 m and is fitted with practical quick-release couplings – for convenient extension and retraction.
Telescopic rod complete 10m	3	4.110-003.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extension and retraction.
iSolar TL 7 H (without hose)	4	4.110-004.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extension and retraction.
Hose solar	5	6.392-978.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.
	6	6.392-977.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.
	7	6.392-976.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.

[■] Included in delivery.

Available accessories.

Extension hose.









		Order Number	Nozzle size			Price	Description	
Wet blasting attachment (without r	nozzle)		1	'				
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0					Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0					Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle pack for wet blasting attach	ment							
Nozzle pack TR wet jet set 0050	3	2.112-023.0	50				Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment .	
Boron carbide nozzle								
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-084.0	6 mm				In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	

[■] Included in delivery.

Available accessories.

Extension hose.











Calca counting		Order Number	Price	De- scripti- on	
Geka coupling With hose nozzle, R 1"	1	6.388-465.0		with hose barb	
Hose coupling	2	6.388-458.0		with female thread	
Suction filter Water filter	3	6.414-956.0		Suitable	
water meet	3	0.717 330.0		for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	
Suction filter with check valve	4	4.730-012.0		Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	

[■] Included in delivery. □ Available accessories. ▲ Extension hose.





		Order Number		Price	De- scripti- on	
Fine-mesh water filter		l		l	I = I	
Fine-mesh water filter with adapter	5	4.730-102.0			Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	

[■] Included in delivery.

Available accessories.

Extension hose.







		Order Number	Price	De- scripti- on
Fine-mesh water filter, 100 μm, R 1"	6	2.638-270.0		Fine- mesh water filter, 100 µm, max. tempe- rature 60°C. Connects to high- pressure cleaner. Protects the high- pressure cleaner from dirt particles contai- ned in the water. Water flow rate up to 1200 I/h. Connec- tor 1".
Water supply hose Water supply hose	7	4.440-207.0		NW 19 R1" / R 3/4", up to 85 °C, for pick-up
	8	4.440-270.0		NW 19 R1" / R1", up to 85 °C

[■] Included in delivery.

Available accessories.

Extension hose.





					De-	
		Order Number		Price	scripti- on	
Backflow check valve			·			
Backflow preventer	9	2.641-374.0			To prevent vent deter-gent getting into the drinking water cycle in case of inlet at low-pressure hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protec-	

[■] Included in delivery.

Available accessories.

Extension hose.











		Order Number	Flow rate		Price	Description	
Push-on washing brush							
Push-on washing brush	1	4.762-497.0				With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.	
Push-on wash brush, M 18 x 1.5	2	4.113-001.0				Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush					 		
Rotating wash brush for > 800 l/h machines, nylon bristles	3	4.113-002.0	800-1300 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 x 1.5 (replaceable brush insert).	
Rotating wash brush for > 800 l/h machines, natural bristles	4	4.113-005.0	800-1300 l/h				

 $[\]blacksquare$ Included in delivery. $\hfill\Box$ Available accessories. $\hfill \triangle$ Extension hose.